

# DATASHEET



## COR70 HIDDEN SASH



<b>ENERGY EFFICIENCY</b>	Uf $\geq$ 1,0 (W/m <sup>2</sup> K) Consult typology, dimension and glass	Thermal Transmission Coefficient
<b>ACCOUSTIC INSULATION</b>	40 mm Rw = 46 dB	Maximum glazing Maximum acoustic insulation
<b>CATEGORIES ACHIEVED AT TEST CENTRE</b>	Class 4 Class E1650 Class C5 Reference test 1.23 x 1.48 m / 1 Sash.	Protection against atmospheric agents Air permeability (UNE-EN 12207) Water tightness (UNE-EN 12208) Wind resistance (UNE-EN 12210)
<b>SECTIONS</b>	70 mm Frame	70 mm Sash
<b>MAXIMUM DIMENSIONS (by sash)</b>	Width (L) = 1300 mm Height (H) = 2400 mm	
<b>MAXIMUM WEIGHT SASH</b>	160 Kg	
<b>EXTRUSION ALLOY</b>	6063 T-5 Profile thickness (Window): 1,9 mm	
<b>POLYAMIDE STRIP LENGTH</b>	Polyamide 6.6 reinforced with 25% fiberglass: 35 mm	
<b>GASKETS</b>	EPDM triple gasket	
<b>FOAMS</b>	Perimeter polyolefin foam in glazing rebate zone	
<b>OPENING POSSIBILITIES</b>	Side hung tilt turn & tilt	INWARD
<b>FINISHES</b>	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating (Qualideco standard) Anodized (According to Ewwa Euras) Optionally bicoloured	

Air permeability  
(UNE-EN 12207):  
Class

4

Wind resistance  
(UNE-EN 12210):  
Class

C5

Water tightness  
(UNE-EN 12208):  
Class

E1650