

DATASHEET



COR VISION



ENERGY EFFICIENCY	Uf $\geq 1,3$ (W/m ² K)	Thermal Transmission Coefficient Consult typology, dimension and glass
--------------------------	------------------------------------	---

ACCOUSTIC INSULATION	30 mm Rw = 41 dB	Maximum glazing Maximum acoustic insulation
-----------------------------	---------------------	--

CATEGORIES ACHIEVED AT TEST CENTRE	Protection against atmospheric agents	
	Class 4	Air permeability (UNE-EN 12207)
	Class 7A	Water tightness (UNE-EN 12208)
	Class C5	Wind resistance (UNE-EN 12210)
	Ensayo de seguridad: PAS24 <input checked="" type="checkbox"/>	Apto Reference test: Balcony 1.23 x 1.55 m, 1 sash + 1 fixed

SECTIONS	116 mm Frame	182 mm Tri-rails	37 mm Sash
-----------------	-----------------	---------------------	---------------

MAXIMUM DIMENSIONS (by sash)	Width (L) = 2500 mm Height (H) = 3000 mm
-------------------------------------	---

MAXIMUM WEIGHT SASH	320 Kg
----------------------------	--------

EXTRUSION ALLOY	6063 T-5
------------------------	----------

PROFILE THICKNESS	Door 1,7 mm
--------------------------	-------------

POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass from 16 a 24 mm
-------------------------------	--

OPENING POSSIBILITIES	Sliding Possibility of 1, 2 or 3 rails Possibility of interior and exterior: corner at 90° without mullion Galandage
------------------------------	---

FINISHES	Colour powder coating (by Qualicoat > 60 micras) Wood effect powder coating (by Qualicoat) Anodized (According to Ewwa Euras) Optionally bicoloured
-----------------	--

Air permeability (UNE-EN 12207):
Class

4

Wind resistance: (UNE-EN 12210):
Class

5

Water tightness (UNE-EN: 12208):
Class

7A