

DATASHEET



SN GARNATA



ENERGY EFFICIENCY	Uf = 0,9 W/(m²K)	Thermal Transmission Coefficient
	Consult typology, dimension and glass	

ACCOUSTIC INSULATION	40 mm	Maximum glazing
	Rw = 42 dB	Maximum acoustic insulation

CATEGORIES ACHIEVED AT TEST CENTRE	Protection against atmospheric agents	
	Class 4	Air permeability (UNE-EN 12207)
	7A	Water tightness (UNE-EN 12208)
	Reference test window 1.23 x 1.48 m / 2 sashes	

CLASSIFICATION	Class A ≥ 2,8 mm	Profile thickness
	Severe Weather	Weather
	Class II	Impact

SECTIONS	170 mm Frame	70 mm Sashi
-----------------	--------------	-------------

MAXIMUM DIMENSIONS (by sash)	Width (L) = 3300 mm
	Height (H) = 2800 mm

MAXIMUM WEIGHT/SASH	Sliding sash up to 300 Kg
----------------------------	---------------------------

GASKETS	PVC double gasket
----------------	-------------------

OPENING POSSIBILITIES	Lift & slide door 1, 2 and 4 sashes
------------------------------	-------------------------------------

FINISHES	White	Coloured wrapping
	Optionally bicoloured	Wood-imitation wrapping

Air permeability
(EN 12207: 2016-12):
Class

4

Profile properties
(Facing impact):
Class

II

Water tightness
(EN 12208: 1999-11):
Class

7A