

DATASHEET



SN MALAKA



ENERGY EFFICIENCY	Uf ≥ 1,3 (W/m²K)	Thermal Transmission Coefficient
	Please consult typology, dimensions and glazing.	

ACCOUSTIC INSULATION	26 mm	Maximum glazing
	Rw = 38 dB	Maximum acoustic insulation

CATEGORIES ACHIEVED AT TEST CENTRE	Protection against atmospheric agents	
	Class 4	Air permeability (UNE-EN 12207)
	Class 7A	Water tightness (UNE-EN 12208)
	Class C5	Wind resistance (UNE-EN 12210)
Reference test window 1.23 x 1.48 m / 2 sashes.		

CLASIFICACION	Class A ≥ 2,5 mm	Profile thickness
	Severe weather	Weather
	Class II	Impac

SECTIONS	70 mm Frame	46 mm Sash
-----------------	-------------	------------

MAXIMUM DIMENSIONS (by sash)	Width (L) = 1400 mm	Window
	Height (H) = 1800 mm	
	Width (L) = 1800 mm	Balcony
	Height (H) = 2600 mm	

MAXIMUM WEIGHT SASH	70 Kg Window	200 Kg Balcony
----------------------------	--------------	----------------

Weather stripping	Built-in double brush Seal
--------------------------	----------------------------

OPENING POSSIBILITIES	Sliding door			
	Two Sashes	Three Sashes	Four Sashes	Six Sashes

FINISHES	Optionally bicoloured White	Coloured wrapping Wood-imitation wrapping
-----------------	-----------------------------	---

Air permeability (UNE-EN 12207):
Class

4

Wind resistance (UNE-EN 12210):
Class

C5

Water tightness (UNE-EN 12208):
Class

7A